



Institute of Hydraulic Engineering and Water Resources Management 




Large Dams

Design, Construction and Performance


Gerald Zenz
Graz - University of Technology

Dam – Design, Construction & Performance – G.Zenz Ljubljana – November - 2008

1

Institute of Hydraulic Engineering and Water Resources Management 

Dam Structures & Geotechnique



Design

Construction / Observation


Operation / Monitoring

Improving / Upgrading

Cooperation & Transfer of Know How

Dam – Design, Construction & Performance – G.Zenz Ljubljana – November - 2008

2


Institute of Hydraulic Engineering and Water Resources Management 

Large Dams – Design, Construction, Operation and Rehabilitation

- Gravity Dams
 - System of Load Transfer
 - Design Issues
 - Sliding Stability
 - Example – HEPP Birecik – Fill and Gravity Dam Structure
- Double Curved Arch Dams
 - Bearing Behaviour
 - Design Aspects
 - Abutment Stability
 - Example – Schlegeis Dam / Austria
 - Example – HEPP Tzankov Kamak / Bulgaria
 - Example – HEPP Ermenek / Turkey
- Pumped Storage Scheme – Limberg II / Pressure Tunnel
- Rehabilitation – Bottom Outlet of Salza Dam


Dam – Design, Construction & Performance – G.Zenz Ljubljana – November - 2008

3


Institute of Hydraulic Engineering and Water Resources Management 

Gravity Type - Dam Structures

Querschnitt



Horizontalschnitt



Gewichtsmauer Gravity Dam (PG) **Pfeilerkopfmauer Buttress Dam (CB)** **Gewölbereihenmauer Multiple Arch Dam (MV)**

Dam – Design, Construction & Performance – G.Zenz Ljubljana – November - 2008

4

TU
Graz

Institute of Hydraulic Engineering and Water Resources Management

Loading Cases

- Dead Weight
- Water Loading, Uplift
- Temperature
- Silt pressure
- Ice Loading
- Wind and Wave
- Earthquake Loading
 - Operating Earthquake OBE
 - Maximum Credible Earthquake
- Structural Alterations

Ljubljana – November - 2008

5

TU
Graz

Institute of Hydraulic Engineering and Water Resources Management

Design Control Measures

Failure Mode

Sliding in any plane in the Abutment –



- In the interface concrete to Rock
- In any possible joint
- In fault system in the Rock
- Tensile- and Compression

Usability – System Performance

- Layout
- Material Parameters
- Permeability

Ljubljana – November - 2008

6



Institute of Hydraulic Engineering and Water Resources Management TU
Graz

Required Safety Margin

$$\tau = \sigma_n \tan \left(\varphi_b + JRC \cdot \log_{10} \frac{JCS}{\sigma_n} \right)$$

$\varphi_b = 29,5^\circ$
Residual Friction Angle / Laboratory

$JRC = 8,3$
Comparison Publication / Field

$JCS = 27,2\text{MPa}$
Laboratory Measurements
Correlation with Schmidt Hammer

Loading Condition	Required Factor of Sliding Safety
Normal operation	1,50
Special loading (e.g. OBE)	1,30
Unusual loading conditions (e.g. MCE)	1,10

Dam – Design, Construction & Performance – G.Zenz Ljubljana – November - 2008

9

Institute of Hydraulic Engineering and Water Resources Management TU
Graz

Selected Hydro Power Plants in Turkey

Ermenek Birecik Karkamis

Muratli Borcka

Deriner

Const. Under Oper. Cons.

Dam – Design, Construction & Performance – G.Zenz Ljubljana – November - 2008

10

TU
Graz

Institute of Hydraulic Engineering and Water Resources Management

Hydro Schemes at the Euphrat

Dam Name	Crest Height (m)	Storage Volume (Mill. m³)	Installed Capacity (MW)
ATATÜRK	168	48,700	2,400
BIRECIK	62.5	1,220	672
KARKAMIS	20.4	157	180
TISHREEN	40	-	352

Birecik first large BOT – Project in Turkey
 Start of Construction April 1996 – Construction Time 66 Month
 River Diversion – June 1999
 Start of Impounding – October 2000
 Commercial Operation Since Oct. 2001

Dam – Design, Construction & Performance – G.Zenz

Ljubljana – November - 2008

11

TU
Graz

Institute of Hydraulic Engineering and Water Resources Management

Hydro Electric Powerplant - Birecik

HPP BIRECIK

Right Embankment Dam | Spillway and Stilling Basin | Left Embankment Dam

Intake Structure and Right Gravity Dam | Powerhouse and Tailrace

Switchyard



Firat River


- Fill Dam (2000m)
 - Clay Core
 - Height 62,5m
- Concrete Dam (500m)
 - Gravity Dam
 - Intake Structure
 - Power House
 - 6x112MW Francis
 - Design Discharge 6x317m³/s ~ 1900m³/s
 - Spillway
 - 10 Sections 12,5m
 - 17500m³/sec Design Flood

Dam – Design, Construction & Performance – G.Zenz


Ljubljana – November - 2008

12



Institute of Hydraulic Engineering and Water Resources Management 

Excavation – Spillway - Intake




Geotechnical Investigations


- Site Mapping
- Drilling Campaign
- Laboratory & In Situ - Tests
- Geophysical Investigation

Dam – Design, Construction & Performance – G.Zenz Ljubljana – November - 2008

15

Institute of Hydraulic Engineering and Water Resources Management 

Joint System – Clay Filled






$\varphi_{\text{clay}} = 22,4^\circ$

Clay Friction Angle / Laboratory


Dam – Design, Construction & Performance – G.Zenz Ljubljana – November - 2008

16




Institute of Hydraulic Engineering and Water Resources Management 

Additional Excavation – Spillway - Intake




Dam – Design, Construction & Performance – G.Zenz Ljubljana – November - 2008

19


Institute of Hydraulic Engineering and Water Resources Management 

Additional Excavation




Dam – Design, Construction & Performance – G.Zenz Ljubljana – November - 2008

20

Institute of Hydraulic Engineering and Water Resources Management 


Operation - Monitoring of Performance




HPP – Birecik	
Design Flow	1900m ³ /s
Hydraulic Head	44m
Capacity	672MW
6 Francis Units	
Annual Production	2500GWh
Entire Length	2510m
Reservoir Volume	1200Mio m ³

Dam – Design, Construction & Performance – G.Zenz Ljubljana – November - 2008

21

Institute of Hydraulic Engineering and Water Resources Management 



Operation – Monitoring Performance




Geodetic Measurements
 Seepage / Uplift
 Displacements – Plump Line / Extensometers / Joint Meters
 Operation – Reservoir Water Level / Downstream Water Level / Temperatures


Dam – Design, Construction & Performance – G.Zenz Ljubljana – November - 2008

22



Institute of Hydraulic Engineering and Water Resources Management 


Arch Dam – Bearing Behavior



The diagram illustrates the bearing behavior of an arch dam. It shows a cross-section of the dam structure (blue and orange) resting on a green foundation. Water is shown on top of the dam. A blue arrow labeled 'Uplift' points upwards from the base of the dam. Another blue arrow labeled 'Seepage' points downwards from the foundation. The foundation is labeled 'Foundation'.


Dam – Design, Construction & Performance – G.Zenz Ljubljana – November - 2008

25

Institute of Hydraulic Engineering and Water Resources Management 

Schlegeis Dam


Crest length	725m
Height	131m
Thickness	34m / 9m
Total Concrete Volume	960000m ³




The photograph shows the Schlegeis Dam, a large concrete arch dam, situated in a deep mountain valley. The dam is curved and spans across the valley. In the background, there are snow-capped mountains and a lake behind the dam.

Dam – Design, Construction & Performance – G.Zenz Ljubljana – November - 2008

26


Institute of Hydraulic Engineering and Water Resources Management 

Dam Excavation




Dam – Design, Construction & Performance – G.Zenz Ljubljana – November - 2008

27

Institute of Hydraulic Engineering and Water Resources Management 

Method of Construction



Individual Columns



- Maximum Height Difference
- Placing Temperature
- Joint Grouting



Monolithic Arch Structure



- Loading Conditions

Dam – Design, Construction & Performance – G.Zenz Ljubljana – November - 2008

28









Institute of Hydraulic Engineering and Water Resources Management TU
Graz

DYNAMIC BEHAVIOUR

- Measured Eigenfrequencies and Mode Shapes

Water Level 7m below crest	
Measured	Calculated
1,92	1,81
2,05	1,86
2,50	2,38

Mode: Eigenfrequenz Linear Balken - Mode: 1; Faktor = 227,79; Phase = 0,0000; (top/bottom)
Deformed View: 0; Deformation Scale Factor: 1,0E+05



Mode: Eigenfrequenz Linear Balken - Mode: 2; Faktor = 204,10; Phase = 0,0000; (top/bottom)
Deformed View: 0; Deformation Scale Factor: 1,0E+05

Dam – Design, Construction & Performance – G.Zenz
Ljubljana – November - 2008

35



Institute of Hydraulic Engineering and Water Resources Management TU
Graz


Added Mass – Versus – Fluid Structure Interaction



Dam – Design, Construction & Performance – G.Zenz
Ljubljana – November - 2008

36



Institute of Hydraulic Engineering and Water Resources Management 


Arch Dam Behavior – ICOLD Benchmark

- measurements provided
- linear + nonlinear benchmark
- ICOLD – Dam Analysis

Dam – Design, Construction & Performance – G.Zenz Ljubljana – November - 2008

39

Institute of Hydraulic Engineering and Water Resources Management 

Sixth Benchmark Workshop on NUMERICAL ANALYSIS OF DAMS

October 17 - 19, 2001
Salzburg, Austria

Theme A: Concrete Dams
Evaluation of Alkali Aggregate Reaction
Formulator: ENEL-Hydro

Theme B: Embankment Dams
Prediction of reflection of C.F.R.D.
Formulator: Coyne & Bellier

Theme C: Interpretation of Measurement Results
Measurements of Schlegeis Arch Dam
Formulator: Verbundplan

Dam – Design, Construction & Performance – G.Zenz Ljubljana – November - 2008

40

INTEGRITY ASSESSMENT OF LARGE CONCRETE DAMS



NW-IALAD

▶ **NETWORK MANAGEMENT**




▶ **DAM CALCULATION**
 ▶ **DAM PERFORMANCE**
 ▶ **DAM MAINTENANCE**
 ▶ **DAM SAFETY**


<http://nw-ialad.uibk.ac.at>

EUROPEAN RESEARCH NETWORK FUNDED BY THE EC

Institute of Hydraulic Engineering and Water Resources Management



Tsankov Kamak - Dam Concreting under Progress



Double Curved Arch Dam



Arch Dam Height	125 m
Crest Length	457 m
Concrete Volume	529.000 m ³

Reservoir:


Max. Flood Level	687.30 m
Max. Op. Level	685.00 m
Min. Op. Level	670.00 m
Total Storage Volume	111 Mio.m ³
Active Storage Volume	41 Mio.m ³

Dam – Design, Construction & Performance – G.Zenz
Ljubljana – November - 2008

42




Institute of Hydraulic Engineering and Water Resources Management 



Dam – Design, Construction & Performance – G.Zenz Ljubljana – November - 2008

45

Institute of Hydraulic Engineering and Water Resources Management 

Abutment Forces










Figure 4: Section through abutment block reaction forces – G+W685+Ts


Dam – Design, Construction & Performance – G.Zenz Ljubljana – November - 2008

46








Institute of Hydraulic Engineering and Water Resources Management 


Model of Structure and Water




- Nonlinear Dynamic Analysis**
 - Joint at the Abutment
 - Block Joints
 - Construction Joints
- Implicit Direct Time Integration**
 - Massless Rock
 - Reservoir Modeled
 - FSI – analysis
 - Acceleration time history

Dam – Design, Construction & Performance – G.Zenz Ljubljana – November - 2008

53

Institute of Hydraulic Engineering and Water Resources Management 


Nonlinear Dynamic Analyses




Step: Step 3
Increment 40; Step Time = 1.990
Deformed Var: U Deformation Scale Factor = 1.900e+02

Dam – Design, Construction & Performance – G.Zenz Ljubljana – November - 2008

54

Institute of Hydraulic Engineering and Water Resources Management 




August – 2008



Quality Assurance

- During Execution of Construction
- Rock Abutment (Geological Monitoring)
- Concrete Production / Surface / Core
- Grouting
- Temperature Distribution

Dam – Design, Construction & Performance – G.Zenz Ljubljana – November - 2008

55

Institute of Hydraulic Engineering and Water Resources Management 



August – 2008

Dam – Design, Construction & Performance – G.Zenz Ljubljana – November - 2008

56


Institute of Hydraulic Engineering and Water Resources Management 




August – 2008

Dam – Design, Construction & Performance – G.Zenz Ljubljana – November - 2008

57

Institute of Hydraulic Engineering and Water Resources Management 


HPP Ermenek – Arch Dam Design and Construction




Reservoir Volume:	4600 Mio m³	Concrete Volume:	289.000 m³
Gross Height:	361 m	Dam Height:	218 m
Capacity:	300 MW	Crest Length:	120 m
Annual Production:	1014 GWh	Dam Thickness:	Crest 7m
Investment:	540 Mio Eur		Base 25m

Dam – Design, Construction & Performance – G.Zenz Ljubljana – November - 2008

58

Institute of Hydraulic Engineering and Water Resources Management 


Pressure Tunnel



Tunnel Boring Maschine
Excav. Diameter 6,7m
Geology
Limestone
Karst
Flysh
Water intrusion

Dam – Design, Construction & Performance – G.Zenz Ljubljana – November - 2008

61

Institute of Hydraulic Engineering and Water Resources Management 


Tunnel - Durchschlag




Ausbruchsfortschritt
Max. Tagesleistung
62m/Tag
Max.Monatsleistung
1004m / Monat

Dam – Design, Construction & Performance – G.Zenz Ljubljana – November - 2008

62

Institute of Hydraulic Engineering and Water Resources Management 


Tunnel Durchschlag




8100m Gesamtlänge
Beginn
26th July 2003
Durchschlag
2nd April 2005

Dam – Design, Construction & Performance – G.Zenz Ljubljana – November - 2008

63

Institute of Hydraulic Engineering and Water Resources Management 

Power Station



Switch Yard

Power House



Ermenek
NQ ~15m³/s
MQ ~43m³/s

Dam – Design, Construction & Performance – G.Zenz Ljubljana – November - 2008

64

Institute of Hydraulic Engineering and Water Resources Management TU
Graz

Switch Yard


Stability
Design – Reliefe Wells

Dam – Design, Construction & Performance – G.Zenz
Ljubljana – November - 2008

65

Institute of Hydraulic Engineering and Water Resources Management TU
Graz

Valve Chamber – Surge Tank




Pressure Tunnel
8,1km

Inclined Shaft
1km


Surge Tank
Diameter 10m
Height ~135m

Dam – Design, Construction & Performance – G.Zenz
Ljubljana – November - 2008

66

Institute of Hydraulic Engineering and Water Resources Management 

Erik Diversion – Ermenek Surge Tank




Erik Addit


Surge Tank - Ermenek

Dam – Design, Construction & Performance – G.Zenz Ljubljana – November - 2008

67

Institute of Hydraulic Engineering and Water Resources Management 

Dam Construction Site - Downstream




Dam – Left Abutment


Galleries GL2 / GL3

Dam – Design, Construction & Performance – G.Zenz Ljubljana – November - 2008

68

Institute of Hydraulic Engineering and Water Resources Management 


Canyon




Depth 200m
Broad – 10 bis 25m
Vertical partly
Steep valley

Dam – Design, Construction & Performance – G.Zenz Ljubljana – November - 2008

69


Institute of Hydraulic Engineering and Water Resources Management 

Gorge





Dam – Design, Construction & Performance – G.Zenz Ljubljana – November - 2008

70

Institute of Hydraulic Engineering and Water Resources Management 

Ermenek - Double Curved Arch Dam




NORMAL OPERATION 694.0 700.00
MINIMUM OPERATION LEVEL 660.0
490.00

Figure 6: General cross section - elevations and water levels

Dam – Design, Construction & Performance – G.Zenz Ljubljana – November - 2008


71

Institute of Hydraulic Engineering and Water Resources Management 

Abutment Forces – Block

Winter and Summer loading condition

Direction and Magnitude are calculated



1R 6R 1M 6L 1L

Dam – Design, Construction & Performance – G.Zenz Ljubljana – November - 2008

72

TU
Graz

Institute of Hydraulic Engineering and Water Resources Management

Hydration Heat Development

$C_{E,FA}$	
Specific heat c	0.92 kJ/(kg·K)
Conductivity k	$11.2 \text{ kJ}/(\text{m}\cdot\text{h}\cdot\text{K}) = 268.8 \text{ kJ}/(\text{m}\cdot\text{d}\cdot\text{K})$
Cement content z	210 kg/m ³
Weight density ρ	2450 kg/m ³
Hydration heat H	343 kJ/kg

adiabatic conditions

Dam – Design, Construction & Performance – G.Zenz
Ljubljana – November - 2008

73

TU
Graz

Institute of Hydraulic Engineering and Water Resources Management



Calculation Parameters		
Height	562	[m a.s.l.]
F	6.60	[m ²]
R	1.45	[m]
A_c	432.1	[m ²]
L	216.0	[m]
K	0.00141	[1/h]
μ	0.00657	[-]
ν	0.685	[-]
C^*	0.985	[-]
β	0.00105	[1/h]
B	0.000604	[1/h]


Table 16: Calculation Parameters; a = 2.0 m; q = 0.3 l/s; 562 m.a.s.l.


Figure 26: Temperature sequence; a = 2.0 m; q = 0.3 l/s; 562 m.a.s.l.

Dam – Design, Construction & Performance – G.Zenz
Ljubljana – November - 2008


74






Institute of Hydraulic Engineering and Water Resources Management 

How a Geologist Sees the Right Bank




Dam – Design, Construction & Performance – G.Zenz Ljubljana – November - 2008

79

Institute of Hydraulic Engineering and Water Resources Management 

Detailed Investigation at Right Abutment



Dam – Design, Construction & Performance – G.Zenz Ljubljana – November - 2008

80

Institute of Hydraulic Engineering and Water Resources Management TU
Graz

Abutment Stability

$$\tau = \sigma_n \tan \left(\varphi_b + JRC \cdot \log_{10} \frac{JCS}{\sigma_n} \right)$$

Possible Sliding Planes
RJ5e and RJ5g

RJ5g (320/80)
 $\varphi_i = 37^\circ + f(JRC)$
 $c_{min} = 0,2MPa$

Dam – Design, Construction & Performance – G.Zenz Ljubljana – November - 2008


81


Institute of Hydraulic Engineering and Water Resources Management TU
Graz

Dam Excavation Right Bank - D/S Key Blocks

Dam – Design, Construction & Performance – G.Zenz Ljubljana – November - 2008

82

Institute of Hydraulic Engineering and Water Resources Management 




D
E
S
I
G
N


E
X
E
C
U
T
I
O
N

Dam – Design, Construction & Performance – G.Zenz Ljubljana – November - 2008

83


Institute of Hydraulic Engineering and Water Resources Management 

Limited Working area at the berms




Dam – Design, Construction & Performance – G.Zenz Ljubljana – November - 2008

84

Institute of Hydraulic Engineering and Water Resources Management 

Anchor drilling from the basket



Dam – Design, Construction & Performance – G.Zenz Ljubljana – November - 2008

85


Institute of Hydraulic Engineering and Water Resources Management 

Adaptation of Appropriate Blasting




Dam – Design, Construction & Performance – G.Zenz Ljubljana – November - 2008

86


Institute of Hydraulic Engineering and Water Resources Management 

Blasting Result





Dam – Design, Construction & Performance – G.Zenz Ljubljana – November - 2008

87

Institute of Hydraulic Engineering and Water Resources Management 


Measurement During Execution




Observational Method

Dam – Design, Construction & Performance – G.Zenz Ljubljana – November - 2008

88

Institute of Hydraulic Engineering and Water Resources Management 



Dam – Design, Construction & Performance – G.Zenz Ljubljana – November - 2008


89

Institute of Hydraulic Engineering and Water Resources Management 




Dam – Design, Construction & Performance – G.Zenz Ljubljana – November - 2008

90

Institute of Hydraulic Engineering and Water Resources Management 

Dam Concreting under Progress




Drainage Curtain


Grout Curtain
Hydraulic Head
23bar

Dam – Design, Construction & Performance – G.Zenz Ljubljana – November - 2008

91

Institute of Hydraulic Engineering and Water Resources Management 


Status of Work



September – 2008

Dam – Design, Construction & Performance – G.Zenz Ljubljana – November - 2008

92

Institute of Hydraulic Engineering and Water Resources Management 

Status of Work


Elevation about 540m a.s.l

Start of Impounding – at ~610m a.s.l

Partial Impounding


Initial Large Increase in Hydraulic Head

- Grouting of Block Joints
- Temperature Distribution



Dam – Design, Construction & Performance – G.Zenz Ljubljana – November - 2008

93


Institute of Hydraulic Engineering and Water Resources Management 

2nd International Conference

LONG TERM BEHAVIOUR OF DAMS
LTBD09

12th – 13th October 2009
Graz, Austria (Europe)

First Announcement



<http://www.ltbd09.tugraz.at>

Topics of the Conference

- Methods of Design and Analysis of Dams
- Experimental Studies
- Dam Monitoring and Instrumentation
- Time Dependent Properties of Construction Materials for Dams and their Constitutive Modelling
- Analytical and Numerical Investigations
- Seepage under Saturated and Unsaturated Conditions
- Dam Foundation and Structure Interactions
- Seismic Aspects and Earthquake Analysis
- Safety Assessment
- Dam Maintenance
- Rehabilitation and Dam Heightening

Dam – Design, Construction & Performance – G.Zenz Ljubljana – November - 2008

94