

# Department of Remote Sensing and Landscape Information Systems University of Freiburg

# **Applications of Laserscanning in Forestry**

by
Christoph Straub
Dr. Holger Weinacker
Yunsheng Wang
Prof. Dr. Barbara Koch

#### **Overview**

- 1. Introduction to ALS in Forestry
- 2. Applications of Laserscanning
  - 2.1 Single Tree Delineation
  - 2.2 Forest Stand Mapping
  - 2.3 Estimation of Forest Characteristics
- 3. Software Demonstration

  TreesVis processing, analyzing and visualisation of laserscanning data






- Faculty of Forest and Environmental Sciences
- University of Freiburg i. Breisgau, Germany
- Teaching and Research:
- → Remote sensing applications in forestry and relevant neighbouring disciplines (e.g. nature conservation, landscape planning)




Freiburg



Why is Airborne Laserscanning (ALS) interresting for forestry?




Raw Data - Profile:




Fullwave, IGI LiteMapper 5600, Summer 2005

DSM:



**Active Surface Algorithm (Weinacker 2004)** 


DTM:



**Active Surface Algorithm (Weinacker 2004)** 



#### **Single Trees:**




- → Estimation of h/d proportion
- → Estimation of stem volume
- → For single trees high point density is required!

Tree Height

Shape


**Single Tree Delineation** 




- → Classification into conifers and deciduous trees; (during winter: penetration rate);
  In boreal forest: differentiation of birch, spruce, pine
- → Species with spectral image data (RGB and CIR)

8

Applications of Laserscanning in Forestry




Forest Stands (management units):



**Tree Number and Stand Density** 

Forest Stands (management units):




- → Applicability of automated harvesting methods
- → Harvester (machine that fells trees, delimbs them and crosscuts them into logs):



 Steepness of terrain and DBH are limiting factors for highly automated harvesters (Heisig et al. 2005)

1470D Rad Harvester
Forsttechnik GmbH (John Deere)
http://www.forstgmbh.at

#### **Forest Roads:**






Local Slope in %: low high

The documentation of the road and path network in the forest:

- → precondition for an optimization of timber transport
- → high importance for soil conservation




**Orthoimage** 



Orthoimage with roads as digitized line features




**Slope image from LIDAR** 



- → Accuracy can be improved
- → With LIDAR additional attributes can be collected e.g. slope per road segment, road width ...

**Applications of Laserscanning in Forestry** 

**Nature Conservation – Biodiversity / Stand Structure:** 




- → Gaps in forest stands are important ecological elements and can support the biodiversity of forest ecosystems
- → Multi-storied forest stands support high diversity and thus biodiversity
- → Modelling of habitat quality


- → In Scandinavia (Norway): LIDAR is already used for forest inventories (Næsset 2002)
- → In Germany: LIDAR for forest inventories is still a research topic; in the moment: terrestrial surveys → expensive
   → LIDAR as an alternative to support or even replace field measurements (?)
- → Orthoimages are used for forest stand mapping (costs are reduced 30-40%)
- Monitoring of forest damages e.g. bavarian national park (insects, fire, windstorm...)

# 2. Applications of Laserscanning

#### 2.1 Automatic Single Tree Delineation



- → A difficult task.
- → No straight lines, no right angles, no planes, overlapping crowns, many different crown shapes and sizes:




Different approaches for automatic single tree delineation – some examples:

- HIGH-SCAN Project: First European wide attempt to derive single tree information from laserscanner data (Hyyppä 2001)
- Swedish Defence Research Agency: Algorithm for boreal trees (Persson 2001, Persson et al. 2002)
- FeLIS: Algorithm developed under German conditions (Koch et al. 2006)
- → "Watershed Segmentation": Segmentation of an image by means of a flooding simulation (Soille 1999)


FeLIS - Single Tree Delineation (main processing steps):

- 1. INPUT: Rasterized laser data (DSM/DTM)
- 2. DSM is smoothed (Gaussian Smoothing)
- 3. Tree tops are extracted (Local Maxima)
- 4. "Pouring Algorithm" (raindrop model)
- 5. Final detection of crown edges by searching vectors from the tree tops → "Ray Algorithm"
- 6. Knowledge-based assumptions on the shape of trees
- → Minimum size
- Minimum distance between tree tops
- → Crown shape (compactness, circularity)


Profile of DSM (individual trees are expected within each salient curve)



#### Pouring (first step) - Local Maxima detection:




#### Pouring (second step) – expansion:



- 1. Maxima are the starting points for an expansion until "valley bottoms" are reached.
- 2. The expansion is done as long as there are chains of pixels in which the gray value gets smaller (like raindrops running downhill from the maxima in all directions)

Result after


"Pouring Operator" (Individual crowns can be expected within each segment. Further analysis are needed to extract the exact shape of crowns)




**Smoothed DSM** 




#### **Extraction of individual crowns (ray algorithm)**





- 1. Assumption: The height change within an individual crown must be continuous
- 2. Virtual rays between the tree tops and border points are generated
- 3. New border points of the tree crown are created if there is an interruption of the continuous height changes by pixels with high difference in elevation

#### Verification of the algorithm (field measurements):



Red: Positions of trees measured with GPS during field work

**Blue: Segmentation result** 

Verification with field measurements:

Coniferous trees (Pseudotsuga menziesii):

No of trees:	Identified correctly:
49	87%

Deciduous trees (Carpinus betulus, Acer pseudoplatanus, Fraxinus excelsior):


No of trees:	Identified correctly:
40	<b>500</b> /
49	50%

(Koch et. al 2006)

- → Verification with 2575 trees
- → 998 trees were indentified (~39%)
- → 74.7 % of timber volume

#### Coniferous trees:

#### **Deciduous trees:**



(from Heurich 2006)


#### **Summary of the verification:**

- Good results for conifers
- Problems with small and suppressed trees
- Stem numbers are underestimated
- Most dominant trees are found (→ trees with high timber volume)
- Crown areas are overestimated

Mean crown area for segmented trees:	
11m²	8.2m <sup>2</sup>

(Koch et. al 2006)

"New Ideas" (Wang 2007):




"Voxel-Model" of point cloud

(dividing the area into small three-dimensional cells).

Layers are created and number of lasercanner points is calculated in each voxel and stored into 2d image.

#### **Digital Forest Stand Maps:**



Forest Area is classified into "management units" based on:

- species
- age
- structure
- composition


Size

Age

Main Tree Species

....


Subdivision of study area into cells (20x20m, nDSM in the background):



#### Classification of the cells based on:


- Percentage of conifers, deciduous trees and forest floor
- → Classes: Conifers-, Deciduous-, Mixed, Forest Floor
- 2. Surface Roughness (variation of height values):
- → Classes: homogeneous, inhomogeneous
- 3. Height Classes:

Dev. Stage	Height
Sapling	3-10 m
Pole	10-15 m
Mature Trees	15-25 m
Old Trees	> 25 m




**Applications of Laserscanning in Forestry** 

Example for stand mapping (during winter (leaf-off) conditions): "Quellgebiet Wieslauter" in the biosphere reserve "Pfälzerwald"



34

STEP 1: Modelling of deciduous and coniferous stands during winter (leaf-off) conditions:



Deciduous Coniferous stand

Winter: First Echo


Winter: Last Echo

STEP 1: Modelling of deciduous and coniferous stands during winter (leaf-off) conditions:


First Echo (nDSM):

All trees

Last Echo (nDSM):




**Coniferous trees** 




**Deciduous trees** 

- → Regions with forest floor
- → Regions with coniferous trees
- → Regions with deciduous trees


...used for classification of cells





"Laserscan-RGB"

"CIR-Orthophoto"



STEP 2: Classification based on variation of height values:

→ coefficient of variation (Cv) of height values in each cell as a measure for the surface roughness


$$C_v = \frac{\sigma}{\mu} \leftarrow$$

 $\sigma$  standard deviation

 $\mu$  mean

... Cv allows comparison of the variation of populations that have significantly different mean values.

## Homogeneous and inhomogeneous canopy structure:







= Regions with "high vertical structure"

## **STEP 3: Height classes based on Top Height:**

$$Top\_Height = \frac{Max(1) + Max(2) + ... + Max(n)}{n}$$




## "Coniferous Forest Cells" classified with height classes:




"juvenile":	h < 3m
"sapling":	3 =< h <10m
"pole":	10 =< h <15m
"mature trees":	15 =< h <25m
"old trees"	25m =< h


## **Grouping of cells:**




Grouping of neighbouring cells within each class into forest stands:



### Result of the automatic delineation into stand units:





 Legend
 Mix h > 25m
 Con h > 25m
 floor & juvenile

 Dec 25m > h > 15m
 Mix 25m > h > 15m
 Con 25m > h > 15m
 h\_struct


 Dec 15m > h > 10m
 Mix 15m > h > 10m
 Con 15m > h > 10m
 v\_struct

 Dec 10m > h > 3m
 Mix 10m > h > 3m
 Con 10m > h > 3m

# 2.2 Forest Stand Mapping – vertical structure analysis

### "Normalization" of Raw Data Points:

 $RawPoint(x,y).Height - DTM(x,y).Height = RawPoint(x,y).Normalized_Height$ 




"Original" point cloud

"Normalized" point cloud

# 2.2 Forest Stand Mapping – vertical structure analysis

### **Height Distribution Function:**



 $\phi(h)$ : Height distribution function


S(h): Smoothed height distribution function

S''(h): Second derivative of S(h)

At the intervals of h where S"(h)<0, there must be salient curves of function S(h);

The intervals of h are considered as height ranges of tree canopy layers.





Size:	1.84ha
Top Height:	23.4m
Developmental Stage:	Mature
Canopy Closure:	99%
Volume:	440m³
Slope:	3 %

# Field Measurements vs. LIDAR

Two possibilities to analyze the data:


 High resolution data → single tree variables can be estimated

2. Low resolution data → plot or forest stand characteristics can be estimated

### **Tree Height (single trees):**

#### Coniferous trees:

#### **Deciduous trees:**




	n	ln	b <sub>0</sub>	b <sub>1</sub>	<b>b</b> <sub>2</sub>	b <sub>3</sub>	b <sub>4</sub>	R <sup>2</sup>	RMSE [m]	VK <sub>RMS</sub> [%]
Laubbäume	371	nein	-1.673	1.125	0.009	0.017	-0.001	0.97	1.25	4.36
Nadelbäume (Hochlage)	169	nein	-1.439	1.268	-0.461	-0.007	0.086	0.99	0.59	2.95
Nadelbäume (Tal- und Hanglage)	281	nein	-0.687	1.081	-0.304	0.000	0.012	0.98	1.19	3.37

(From Heurich 2006)

### **Crown Radius (single trees):**

#### Coniferous trees:

#### **Deciduous trees:**




	n	ln	b <sub>0</sub>	b <sub>1</sub>	b <sub>2</sub>	b <sub>3</sub>	b <sub>4</sub>	R <sup>2</sup>	RMSE [m]	VK <sub>RMS</sub> [%]
Laubbäume	278	ja	1.368	-0.043	0.000	0.005	0.001	0.46	0.79	17.3
Nadelbäume (Hochlage)	160	ja	1.124	-0.073	0.246	0.002	-0.027	0.31	0.32	12.5
Nadelbäume (Tal- und Hanglage)	93	nein	8.223	-0.375	0.183	0.006	-0.018	0.19	0.57	16.1

(From Heurich 2006)

### **DBH** (single trees):

#### **Coniferous trees:**

#### **Deciduous trees:**



~		n	ln	b <sub>0</sub>	<b>b</b> 1	<b>b</b> <sub>2</sub>	b <sub>3</sub>	b <sub>4</sub>	$\mathbb{R}^2$	RMSE [cm]	VK <sub>RMS</sub> [%]
	Laubbäume	368	ja	1.592	0.089	0.081	-0.003	-0.001	0.82	5.84	15.7
	Nadelbäume (Hochlage)	171	ja	1.682	0.087	0.211	-0.001	-0.029	0.90	5.10	14.1
	Nadelbäume (Tal- und Hanglage)	287	ja	1.684	0.074	0.075	0.000	-0.004	0.86	7.90	15.3

(From Heurich 2006)

Standard volume function for single trees:

$$V = \frac{\pi}{4} \cdot (DBHp)^2 \cdot Hp \cdot f$$


V = volume

DBHp = diameter of tree (predicted)

Hp = height of tree (predicted)

f = form factor


### Plotwise approach:



For each georeferenced plot properties from raw data points are extracted and are related to field plot data by regression analysis (→ calibration of regression models)

Properties which may be extracted from ALS data (Næsset 2003):


**Height related variables:** 



**Height-related variables:** 

Percentiles of the heights: hp0, hp10, ...., hp90, hcv, hmean ...

**Density related variables:** 




Densities of 10 vertical layers: d0, d1, ..., d9
Proportions of points above percentiles of
the heights for 0%, 10%, ...90% to total number
of points

### Results of study in Norway (Næsset 2002):

## **Stand Height:**


Figure 1: Scatterplots of observed stand attributes as a function of attributes predicted using regression models estimated from the sample plot inventory



## 


**Timber Volume:** 

Forest Inventories (plotwise) proposed by (Næsset 2003), modified:



### 3.0 Software Demonstration

TreesVis - processing, analyzing and visualisation of laserscanning data



### Literature

Heurich, M. (2006): Evaluierung und Entwicklung von Methoden zur automatisierten Erfassung von Waldstrukturen aus Daten flugzeuggetragener Fernerkundungssensoren, Forstliche Forschungsberichte, München

Heisig (2005): GIS based Forest Biomass Exploitation for Energy Supply in the Northern Black Forest Region, PFG, Schweizerbart'scheVerlagsbuchhandlung, Stuttgart

Hyyppä, J.; Hyyppä, H. (2001): Assessing forest stand attributes by integrated use of high-resolution satellite imagery and laserscanner, High-Scan, Final Report – prepared for European Commission Directorate General XII, Helsinki

Koch, B., Heyder U., Weinacker, H., (2006): Detection of individual tree crowns in airborne LIDAR data. An approach to delineate tree crowns in mixed and deciduous temperate forests. Photogrammetric Engineering and Remote Sensing, 72, (4), pp. 357 – 363

Næsset (2002): Data Acquisition for Forest Planning Using Airborne Laser Scanning, presented at ForestSAT Symposium Heriot Watt University, Edinburgh

Næsset (2003): "Laser scanning in practical forest inventories: the Norwegian inventories: the Norwegian experience",

Online: http://portal.uni-freiburg.de/felis/skripte/download/NLH/view

### Literature

- Persson, A. (2001): Extraction of individual trees using laser radar data. Master Thesis EX013, Chalmers University of Technology, Göteborg, Sweden, 28 p.
- Persson, A., Holmgren, J. and Södermann, U. (2002): Detecting and measuring individual trees using an airborne laser scanner, Photogrammetric Engineering & Remote Sensing; Vol. 68. No. 9. September 2002. S. 925-932.
- Persson, A., Holmgren, J., Södermann, U. (2006): Identification of tree specious of individual trees by combining very high resolution laser data with multi-spectral images, In: Proceedings of the international workshop on 3D remote sensing in forestry, 14th -15th Feb., Vienna
- Soille, P. (1999): Morphological Image Analysis, Springer, Berlin
- Wang, Y. (2007): Development of a procedure for vertical structure analysis and 3D-single tree extraction within forests based on LIDAR point cloud, ISPRS workshop on Laser Scanning 2007, accepted (20th June 07), Finland
- Weinacker, H., Koch, B., Heyder, U., Weinacker, R., (2004): Development of filtering, segementation and modelling modules for LIDAR and multispectral data as a fundament of an automatic forest inventory system In: Laser-Scanners for Forest and Landscape Assessment, International Archives of Photogrammetry, Remote Sensing and Spatial Information Sciences, Vol. XXXVI, 8/W2, Freiburg

### Literature

Weinacker, H.; Koch, B.; Weinacker, R. (2004): TreesVis – A software system for simultaneous 3D-real-time visualization of DTM, DSM, Laser raw data, multispectral data, simple tree and building models, In: Laser-Scanners for Forest and Landscape Assessment, International Archives of Photogrammetry, Remote Sensing and Spatial Information Sciences, Vol. XXXVI, 8/W2, Freiburg